## NSN 5305-00-143-3453

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-3453 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.240 inches **Fastener Length:** Between 0.670 inches and 0.690 inches **Head Style:** Pan **Head Diameter:** 0.275 inches **Head Height:** 0.075 inches **First Diameter From Head:** Between 0.143 inches and 0.149 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.430 inches and 0.455 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4130 or steel comp 4140 **Material Specification:** Aisi assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-143-3453

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0