## NSN 5305-00-143-9574

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-143-9574
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.251 inches and 1.375 inches
Fastener Length:
Between 1.313 inches and 1.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.265 inches and 0.270 inches
Head Height:
Between 0.088 inches and 0.102 inches
Hole Diameter:
0.034 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.164 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th materia
response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Head Hole Configuration Style:
Round

Unjc

**Thread Series Designator:** 

## NSN 5305-00-143-9574

Machine Screw - Page 2 of 2



Specification Data:
80205-nas1101 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Mil-std (military Standard):

Mil-s-5626 spec.

**Fiig:** A500d0