
NSN 5305-00-143-9613

Close Tolerance Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.250 inches and 0.317 inches Fastener Length: Between 0.385 inches and 0.432 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.297 inches and 0.302 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** Between 99.5 degrees and 100.5 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 76823-51b581 manufacturers standard Shelf Life: N/a

NSN 5305-00-143-9613

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

