NSN 5305-00-144-0382

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-144-0382

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.222 inches and 0.262 inches
Fastener Length:
Between 0.407 inches and 0.417 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.052 inches and 0.062 inches
Shoulder Diameter:
0.158 inches first shoulder and 0.159 inches first shoulder
Shoulder Length:
0.135 inches first shoulder and 0.145 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round first shoulder
Special Features:
Thread relief groove 0.020 in. Min to 0.040 in. Maximum width cut to 0.085 in. Min to 0.095 in. Maximum dia
Material:
Steel comp 303
Material Specification:
Astm a582, cond a assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-144-0382

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0