## NSN 5305-00-144-0596

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-144-0596

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.342 inches and 0.392 inches
Fastener Length:
Between 0.550 inches and 0.590 inches
Head Style:
Pan
Head Diameter:
Between 0.361 inches and 0.385 inches
Head Height:
Between 0.103 inches and 0.118 inches
Shoulder Diameter:
0.186 inches first shoulder and 0.189 inches first shoulder
Shoulder Length:
0.198 inches first shoulder and 0.208 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round first shoulder
Material:
Steel comp 8630 or steel comp 4037
Material Specification:
Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-00-144-0596

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.