NSN 5305-00-144-1491

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-144-1491 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.447 inches **Fastener Length:** Between 2.078 inches and 2.125 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.377 inches and 0.381 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037 or steel comp 4130 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-144-1491

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0