NSN 5305-00-144-8362

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-144-8362 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.400 inches **Fastener Length:** Between 2.298 inches and 2.328 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.577 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.928 inches and 1.948 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy **Material Specification:** Nas621, 6al-4v assn standard single material response or ams 4928 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1155 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-144-8362

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0