## NSN 5305-00-145-0780

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-145-0780 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.322 inches **Fastener Length:** Between 0.740 inches and 0.770 inches **Head Style:** Pan **Head Diameter:** 0.322 inches **Head Height:** 0.115 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.418 inches and 0.468 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-145-0780

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0