

View Online at <https://aerobasegroup.com/nsn/5305-00-145-0863>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.198 inches and 0.224 inches

**Fastener Length:**

Between 0.359 inches and 0.375 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.118 inches and 0.130 inches

**Hole Diameter:**

0.046 inches

**First Diameter From Head:**

Between 0.137 inches and 0.139 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.151 inches and 0.161 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hole Configuration Style:**

Round

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.