

View Online at <https://aerobasegroup.com/nsn/5305-00-145-0863>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.198 inches and 0.224 inches

Fastener Length:

Between 0.359 inches and 0.375 inches

Head Style:

Fillister

Head Diameter:

Between 0.292 inches and 0.313 inches

Head Height:

Between 0.118 inches and 0.130 inches

Hole Diameter:

0.046 inches

First Diameter From Head:

Between 0.137 inches and 0.139 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.151 inches and 0.161 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hole Configuration Style:

Round

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.