Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-145-0920

1	Fhread Class:
2	2a
٦	Thread Direction:
F	Right-hand
٦	Thread Length:
C	0.300 inches
F	Fastener Length:
C	0.620 inches
ŀ	lead Style:
F	Pan
ŀ	lead Diameter:
E	Between 0.256 inches and 0.270 inches
ŀ	lead Height:
E	Between 0.087 inches and 0.097 inches
F	First Diameter From Head:
E	Between 0.098 inches and 0.102 inches
6	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
C	0.320 inches
I	nternal Drive Style:
C	Cross recess type 1
٦	Thread Diameter:
C	0.138 inches
٦	Thready Qty Per Inch (tpi):
3	32
E	Externally Relieved Body Diameter Quantity:
1	
S	Special Features:
8	32 degree cone point
N	Naterial:
	Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303f or steel comp 303 plus x or steel comp
	303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp
	310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323
	or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or stainless steel
	Surface Treatment:
	Passivate
	Surface Treatment Specification:
	Qq-p-35 federal specification single treatment response
	Thread Series Designator:
	Jnc
	Shelf Life:
	√a
ι	Jnit Of Measure:
-	
	Demilitarization:
N	

NSN 5305-00-145-0920

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

