Externally Relieved Body Screw - Page 1 of 1

AeroBase

View Online at https://aerobasegroup.com/nsn/5305-00-145-0922

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.230 inches a	nd 0.270 inches
Fastener Length:	
Between 0.605 inches a	nd 0.645 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.306 inches a	nd 0.322 inches
Head Height:	
Between 0.105 inches a	nd 0.115 inches
First Diameter From H	ead:
Between 0.115 inches a	nd 0.125 inches
Distance From Larges	t Bearing Surface Of Head To End Of First Diameter:
Between 0.335 inches a	nd 0.415 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.164 inches	
Thready Qty Per Inch	tpi):
32	
Externally Relieved Bo	ody Diameter Quantity:
1	
Material:	
Steel comp 301 or stee	I comp 302 or steel comp 302b or steel comp 303 or steel comp 303f or steel comp 303 plus x or steel comp 304
or steel comp 3041 or s	teel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or
steel comp 314 or stee	comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel
comp 347 or steel com	o 348 or steel comp 384 or steel comp 385 or stainless steel
Surface Treatment:	
Passivate	
Surface Treatment Sp	ecification:
Qq-p-35 federal specific	ation single treatment response
Thread Series Designa	itor:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
4003b0	