

View Online at <https://aerobasegroup.com/nsn/5305-00-145-0944>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.231 inches and 0.312 inches

**Fastener Length:**

Between 0.281 inches and 0.312 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.208 inches and 0.226 inches

**Head Height:**

Between 0.089 inches and 0.096 inches

**Hole Diameter:**

0.046 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material:**

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 or steel

**Screw Surface Treatment:**

Cadmium or chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2 cl 3 federal specification all treatment responses

**Head Hole Configuration Style:**

Round

**Thread Series Designator:**

Unf

**Specification Or Standard:**

1 type and 5s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0