## NSN 5305-00-146-2560

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-146-2560 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.255 inches **Fastener Length:** 0.812 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.296 inches and 0.328 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.463 inches and 0.473 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style no. 6 0.094 in. Nom Ig, 0.079 in. Min to 0.095 in. Maximum dia, 90.0 degree nom point angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-146-2560

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0