NSN 5305-00-146-2666

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-146-2666 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 1.344 inches and 1.406 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.750 inches **Head Height:** 0.625 inches **First Diameter From Head:** 0.562 inches **Second Diameter From Head:** Between 0.170 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.000 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Gps10.030 operation 21a, fscm 24930 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-146-2666

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0