

View Online at <https://aerobasegroup.com/nsn/5305-00-146-3193>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.315 inches

**Fastener Length:**

Between 1.555 inches and 1.585 inches

**Head Diameter:**

0.563 inches

**Head Height:**

0.100 inches

**Width Between Flats:**

0.460 inches

**Shoulder Diameter:**

0.434 inches first shoulder and 0.435 inches first shoulder

**Shoulder Length:**

1.210 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.158 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.440 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Ams-5629type ph13-8mo assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Stf0168 fsc-76823 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0