## NSN 5305-00-146-7119

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-146-7119 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.245 inches **Fastener Length:** Between 0.984 inches and 1.016 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.620 inches and 0.630 inches **Head Height:** Between 0.224 inches and 0.276 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.615 inches and 0.635 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Point style no. 6 0.125 in. Nom long 60.0 degree nom point angle 0.104 in. Min 0.120 in. Maximum dia Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-25 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-146-7119

Externally Relieved Body Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0