NSN 5305-00-146-7192

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-146-7192

Thread Class:	
3а	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.423 inc	hes and 0.473 inches
Fastener Length:	
Between 1.808 inc	hes and 1.838 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.531 inc	hes and 0.558 inches
Grip Diameter:	
Between 0.3115 in	ches and 0.3120 inches
Internal Drive Sty	le:
Offset cruciform (to	rque set)
Thread Diameter:	
0.312 inches	
Grip Length:	
Between 1.365 inc	hes and 1.385 inches
Thready Qty Per I	nch (tpi):
24	
Min. Tensile Strer	ıgth (psi):
160000 pounds pe	r square inch
Countersink Angl	e:
Between 59.75 dec	grees and 60.25 degrees
Surface Finish:	
32.0 microinches th	reads
Special Features:	
Bearing surface of	head grooved to 0.394 in. Min 0.396 in. Maximum dia, 0.092 in. Min 0.097 in. Maximum Ig from top of hea
Material:	
Titanium alloy uns	r54520
Material Specifica	tion:
Nas621, comp 6al-	4v assn standard single material response
Thread Series Des	signator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5305-00-146-7192

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

