

View Online at <https://aerobasegroup.com/nsn/5305-00-147-6175>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.481 inches and 0.562 inches

**Fastener Length:**

Between 0.531 inches and 0.562 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: helicopter, carrier based asw, sh-60f; helicopter, seahawk, h-60; aircraft, tomcat f-14; helicopter, seasprite h-2; aircraft, viking s-3b; helicopter, iroquois hh/uh-1; helicopter, sea king h-3; helicopter, sea knight h-46; aircraft, hornet f/a-18; helicopter, advance attack, ah-1w

**Thread Diameter:**

0.112 inches

**Thread Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Screw Material:**

Copper alloy

**Screw Material Specification:**

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 9c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0