

View Online at <https://aerobasegroup.com/nsn/5305-00-147-6175>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.481 inches and 0.562 inches

Fastener Length:

Between 0.531 inches and 0.562 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: helicopter, carrier based asw, sh-60f; helicopter, seahawk, h-60; aircraft, tomcat f-14; helicopter, seasprite h-2; aircraft, viking s-3b; helicopter, iroquois hh/uh-1; helicopter, sea king h-3; helicopter, sea knight h-46; aircraft, hornet f/a-18; helicopter, advance attack, ah-1w

Thread Diameter:

0.112 inches

Thread Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy

Screw Material Specification:

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0