NSN 5305-00-147-6392

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-147-6392 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.530 inches and 0.590 inches **Fastener Length:** Between 2.906 inches and 3.000 inches **Head Style:** Thumb no. 7 **Head Height:** Between 0.480 inches and 0.554 inches Width Between Flats: Between 1.350 inches and 1.410 inches **First Diameter From Head:** Between 0.175 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 2.316 inches and 2.470 inches **Point Style:** Flat **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Wing matl steel aisi 347 Material: Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316l o comp 310 or steel comp 309 or steel comp 305 or steel comp 304 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-147-6392

Thumbscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0