NSN 5305-00-150-3088

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-150-3088



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.294 inches and 0.375 inches

Fastener Length:

Between 0.344 inches and 0.375 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

140000 pounds per square inch

Hardness Rating:

Between 248.0 brinell standard and 341.0 brinell standard

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams 5732 assn standard single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 t4 2 cl 3 federal specification all treatment responses

Thread Series Designator:

Unjc

Specification Data:

80205-nas1100 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-150-3088 Machine Screw - Page 2 of 2

Fiig: A500d0

