NSN 5305-00-150-3089

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-3089 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.438 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 24.0 rockwell c and 35.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1100 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-150-3089 Machine Screw - Page 2 of 2



Fiig:

A500d0