## NSN 5305-00-150-3202

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-150-3202 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.907 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel or steel **Screw Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Thread undercut 0.300 in. Long starting 0.100 in. From thread end **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:**