

View Online at <https://aerobasegroup.com/nsn/5305-00-150-3242>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.427 inches and 0.494 inches

**Fastener Length:**

Between 1.874 inches and 1.921 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.720 inches and 0.754 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Shank Unthreaded Hole Diameter:**

0.107 inches first hole

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.427 inches and 1.447 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.735 inches and 1.814 inches first hole

**Product Name:**

Navy special project

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0