

View Online at <https://aerobasegroup.com/nsn/5305-00-150-3242>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.427 inches and 0.494 inches

Fastener Length:

Between 1.874 inches and 1.921 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.720 inches and 0.754 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Shank Unthreaded Hole Diameter:

0.107 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.500 inches

Grip Length:

Between 1.427 inches and 1.447 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.735 inches and 1.814 inches first hole

Product Name:

Navy special project

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0