## NSN 5305-00-150-3264

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-3264

View Online at https://aerobasegroup.com/nsn/5305-00-150-3264
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.250 inches and 0.317 inches
Fastener Length:
Between 0.510 inches and 0.557 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.270 inches and 0.302 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.377 inches first hole and 0.456 inches first hole
Material:
Steel comp h11
Material Specification:
Ams6485 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:

Unjf

## NSN 5305-00-150-3264

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0