

View Online at <https://aerobasegroup.com/nsn/5305-00-150-3265>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.250 inches and 0.317 inches

**Fastener Length:**

Between 0.385 inches and 0.432 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.270 inches and 0.302 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.115 inches and 0.135 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.250 inches first hole and 0.331 inches first hole

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0