## NSN 5305-00-150-3280

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-3280 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.357 inches **Fastener Length:** Between 1.238 inches and 1.285 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.469 inches and 0.474 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-00-150-3280

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.