NSN 5305-00-150-3282

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-150-3282



Thread Class: 3a

Thread Direction:

Right-hand

Thread Length:

Between 0.283 inches and 0.323 inches

Fastener Length:

Between 0.365 inches and 0.385 inches

Head Style:

Double hexagon w/ hole

Head Height:

Between 0.220 inches and 0.240 inches

Width Between Flats:

0.219 inches

Extended Washer Diameter:

Between 0.302 inches and 0.322 inches

Extended Washer Thickness:

0.030 inches

Hole Diameter:

0.047 inches

Thread Diameter:

0.164 inches

Hole Quantity:

4

Thready Qty Per Inch (tpi):

36

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

Between 248.0 brinell standard and 341.0 brinell standard

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams 5731 assn standard single material response

Screw Surface Treatment:

Silver

Screw Surface Treatment Specification:

Ams 2411 assn standard single treatment response

Head Hole Configuration Style:

Double hexagon longitudinal hole

Thread Series Designator:

Unjf

NSN 5305-00-150-3282

Machine Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

