NSN 5305-00-150-3319

Between 0.350 inches and 0.400 inches

Between 0.735 inches and 0.765 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Head Style:

Pan

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-3319

| Head Diameter: | |
|---|--|
| Between 0.594 inches and 0.615 inches | |
| Head Height: | |
| Between 0.203 inches and 0.218 inches | |
| Grip Diameter: | |
| Between 0.3110 inches and 0.3120 inches | |
| Internal Drive Style: | |
| Offset cruciform (torque set) | |
| Thread Diameter: | |
| 0.312 inches | |
| Grip Length: | |
| Between 0.365 inches and 0.385 inches | |
| Thready Qty Per Inch (tpi): | |
| 24 | |
| Min. Tensile Strength (psi): | |
| 140000 pounds per square inch | |
| Hardness Rating: | |
| 248.0 brinell standard and 341.0 brinell standard | |
| Surface Finish: | |
| 32.0 microinches threads | |
| Product Name: | |
| Navy special project | |
| Material: | |
| Iron alloy 660 | |
| Material Specification: | |
| Ams 5732 assn standard single material response | |
| Surface Treatment: | |
| Passivate | |
| Surface Treatment Specification: | |
| Qq-p-35 federal specification single treatment response | |
| Thread Series Designator: | |
| Unjf | |

NSN 5305-00-150-3319

Close Tolerance Screw - Page 2 of 2



| Spe | cific | ation | Data: |
|-----|-------|-------|-------|
|-----|-------|-------|-------|

80205-nas1135 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0