

View Online at <https://aerobasegroup.com/nsn/5305-00-150-3319>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.350 inches and 0.400 inches

**Fastener Length:**

Between 0.735 inches and 0.765 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.594 inches and 0.615 inches

**Head Height:**

Between 0.203 inches and 0.218 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Navy special project

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1135 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0