## NSN 5305-00-150-3365

Shoulder Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-150-3365

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.316 inches
Fastener Length:
Between 1.291 inches and 1.321 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.490 inches and 0.510 inches
Head Height:
Between 0.080 inches and 0.090 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Distance From Head Largest Bearing Surface To Shank Hole Center:
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> 1.175 inches first hole and 1.205 inches first hole
1.175 inches first hole and 1.205 inches first hole
1.175 inches first hole and 1.205 inches first hole Special Features:
1.175 inches first hole and 1.205 inches first hole <b>Special Features:</b> Shoulder 16 microinch finish
1.175 inches first hole and 1.205 inches first hole <b>Special Features:</b> Shoulder 16 microinch finish <b>Material:</b>
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> </ul>
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> <li>Surface Treatment:</li> </ul>
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> <li>Surface Treatment:</li> <li>Cadmium head</li> </ul>
1.175 inches first hole and 1.205 inches first hole Special Features: Shoulder 16 microinch finish Material: Steel comp h11 Surface Treatment: Cadmium head Surface Treatment Specification:
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> <li>Surface Treatment:</li> <li>Cadmium head</li> <li>Surface Treatment Specification:</li> <li>Nas672 assn standard single treatment response threads</li> </ul>
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> <li>Surface Treatment:</li> <li>Cadmium head</li> <li>Surface Treatment Specification:</li> <li>Nas672 assn standard single treatment response threads</li> <li>Thread Series Designator:</li> </ul>
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> <li>Surface Treatment:</li> <li>Cadmium head</li> <li>Surface Treatment Specification:</li> <li>Nas672 assn standard single treatment response threads</li> <li>Thread Series Designator:</li> <li>Unjf</li> </ul>
<ul> <li>1.175 inches first hole and 1.205 inches first hole</li> <li>Special Features:</li> <li>Shoulder 16 microinch finish</li> <li>Material:</li> <li>Steel comp h11</li> <li>Surface Treatment:</li> <li>Cadmium head</li> <li>Surface Treatment Specification:</li> <li>Nas672 assn standard single treatment response threads</li> <li>Thread Series Designator:</li> <li>Unjf</li> <li>Shelf Life:</li> </ul>
1.175 inches first hole and 1.205 inches first hole <b>Special Features:</b> Shoulder 16 microinch finish <b>Material:</b> Steel comp h11 <b>Surface Treatment:</b> Cadmium head <b>Surface Treatment Specification:</b> Nas672 assn standard single treatment response threads <b>Thread Series Designator:</b> Unjf <b>Shelf Life:</b> N/a
1.175 inches first hole and 1.205 inches first hole <b>Special Features:</b> Shoulder 16 microinch finish <b>Material:</b> Steel comp h11 <b>Surface Treatment:</b> Cadmium head <b>Surface Treatment Specification:</b> Nas672 assn standard single treatment response threads <b>Thread Series Designator:</b> Unjf <b>Shelf Life:</b> N/a
1.175 inches first hole and 1.205 inches first hole Special Features: Shoulder 16 microinch finish Material: Steel comp h11 Surface Treatment: Cadmium head Surface Treatment Specification: Nas672 assn standard single treatment response threads Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:
1.175 inches first hole and 1.205 inches first hole Special Features: Shoulder 16 microinch finish Material: Steel comp h11 Surface Treatment: Cadmium head Surface Treatment Specification: Nas672 assn standard single treatment response threads Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No
1.175 inches first hole and 1.205 inches first hole Special Features: Shoulder 16 microinch finish Material: Steel comp h11 Surface Treatment: Cadmium head Surface Treatment Specification: Nas672 assn standard single treatment response threads Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:  Demilitarization: