## NSN 5305-00-150-3403

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-3403 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.734 inches **Fastener Length:** 1.656 inches **Head Style:** Hexagon **Head Height:** 0.120 inches Width Between Flats: Between 0.245 inches and 0.250 inches **First Diameter From Head:** Between 0.122 inches and 0.124 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.780 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 201000 pounds per square inch Hardness Rating: 43.0 rockwell c and 46.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses

**Thread Series Designator:** Unc

## NSN 5305-00-150-3403

Externally Relieved Body Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
N.I.
No
Fiig:

Mil-std (military Standard):

Mil-s-5000 spec.

Shelf Life: