NSN 5305-00-150-3584

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-3584 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 2.391 inches and 2.421 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.382 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.990 inches and 2.010 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp 4130 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjf 80205-nas583 professional/industrial association standard

Specification Data: Shelf Life:

N/a

NSN 5305-00-150-3584

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0