NSN 5305-00-150-3599

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-150-3599



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.654 inches and 0.735 inches Fastener Length: Between 0.950 inches and 1.001 inches **Head Style:** Pan **Head Diameter:** Between 0.716 inches and 0.740 inches **Head Height:** Between 0.244 inches and 0.261 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Product Name:** Navy special project **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-150-3599

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

