NSN 5305-00-150-4794

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-4794 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.297 inches **Fastener Length:** Between 0.640 inches and 0.672 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.296 inches and 0.328 inches **Head Height:** Between 0.172 inches and 0.204 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.343 inches and 0.407 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-00-150-4794

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0