Externally Relieved Body Screw - Page 1 of 1

AeroBase

View Online at https://aerobasegroup.com/nsn/5305-00-150-4950

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.270 inches and 0.290 inche	rS
Fastener Length:	
Between 0.719 inches and 0.750 inche	is
Head Style:	
Pan	
Head Diameter:	
Between 0.306 inches and 0.322 inche	rS
Head Height:	
Between 0.105 inches and 0.115 inche	rS
First Diameter From Head:	
Between 0.115 inches and 0.125 inche	iS
Distance From Largest Bearing Surf	ace Of Head To End Of First Diameter:
Between 0.429 inches and 0.480 inche	iS
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.164 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Diameter (	Quantity:
1	
Material:	
Steel comp 301 or steel comp 302 or	steel comp 440f or steel comp 303 or steel comp 303f or steel comp 303 plus x or steel comp
303se or steel comp 304 or steel com	ap 3041 or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp
310 or steel comp 310s or steel comp	314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323
or steel comp 324 or steel comp 347	or steel comp 348 or steel comp 384 or steel comp 385
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single tre	atment response
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
4003b0	