NSN 5305-00-150-4951

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-150-4951 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.270 inches and 0.290 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.554 inches and 0.605 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303f or steel comp 303 plus x or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

Demilitarization: