NSN 5305-00-150-9209

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-150-9209 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.719 inches and 0.844 inches **Fastener Length:** 0.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unf

N/a

Shelf Life:

NSN 5305-00-150-9209

Machine Screw - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.