

View Online at <https://aerobasegroup.com/nsn/5305-00-150-9264>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.984 inches and 1.079 inches

**Fastener Length:**

1.125 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.309 inches and 0.414 inches

**Head Height:**

Between 0.161 inches and 0.170 inches

**Hole Diameter:**

Between 0.061 inches and 0.066 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Screw Material:**

Steel comp 8630

**Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Head Hole Configuration Style:**

Hexagon flats

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.