# NSN 5305-00-150-9264

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-150-9264



Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.984 inches and 1.079 inches

#### Fastener Length:

1.125 inches

Head Style:

Fillister

Head Diameter:

Between 0.309 inches and 0.414 inches

#### **Head Height:**

Between 0.161 inches and 0.170 inches

#### Hole Diameter:

Between 0.061 inches and 0.066 inches

#### **Internal Drive Style:**

Cross recess type 1

### Thread Diameter:

0.250 inches

#### Hole Quantity:

1

# Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### Screw Material:

Steel comp 8630

#### **Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

#### Screw Surface Treatment:

Cadmium

#### Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

## Head Hole Configuration Style:

Hexagon flats

### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

# NSN 5305-00-150-9264

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

