## NSN 5305-00-150-9464

Machine Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-150-9464

3a         Thread Direction:         Right-hand         Thread Longth:         Between 0.725 inches and 0.844 inches         Fastener Longth:         0.875 inches         Head Sigle:         Fillister         Head Sigle:         Fillister         Head Sigle:         Between 0.250 inches and 0.270 inches         Head Height:         Between 0.106 inches and 0.113 inches         Head Height:         Ode Indenter:         0.464 inches         Hord Diameter:         0.464 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.464 inches         Hole Quantity:         1         Thread Style Per Inch (rpi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness         Sterew Material:         Sterewein Sterewein Sterewein Sterew	Thread Class:	
Right-hand         Thread Length:         Between 0.725 inches and 0.844 inches         Fastener Length:         0.875 inches         Head Siyle:         Fillister         Head Diameter:         Between 0.250 inches and 0.270 inches         Head Height:         Between 0.260 inches and 0.113 inches         Hold Diameter:         0.046 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.144 inches         Hole Quantity:         1         Thread View Per Inch (tpi):         36         Between 0.200 conckwell c and 32.0 rockwell c         Screw Material:         Steel comp 8630         Screw Variael Treatment:         Quanti         Gamin         Grey Strice Treatment:         Cadmin         Grey Waterial Specification single material response or an-s-9 military standard single material response         Screw Surface Treatment:         Cadmin         Screw Surface Treatment:         Cadmin         Screw Surface Treatment:         Cadmin         Screw Stris Configuation Single treatment response	3a	
Thread Length: Between 0.725 inches and 0.844 inches Fastener Length: 0.875 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches Hole Diameter: 0.464 inches Hole Diameter: 0.464 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.464 inches Hole Quantity: 1 Thread Juaneter: 0.464 inches Hole Quantity: 1 Thread Juaneter: 0.464 inches Hole Quantity: 1 Steel Comp Style: Sterw Material Steength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment: Cadmium Screw Surface Treatment: Cadmium Screw Surface Treatment: Cadmium	Thread Direction:	
Between 0.725 inches and 0.844 inches         Fastener Length:         0.875 inches         Head Style:         Fillister         Head Style:         Fillister         Head Diameter:         Between 0.250 inches and 0.270 inches         Head Height:         Between 0.106 inches and 0.113 inches         Hole Diameter:         0.404 linches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thready Qty Per Inch (tpi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness Rating:         Between 26.0 rockwell c and 32.0 rockwell c         Screw Material:         Stel comp 8630         Screw Material Specification:         Mil-se050 military specification single material response or an-s-9 military standard single material response         Screw Surface Treatment:         Cadmium         Q-p-416, type 1, cl 3 federal specification         Q-p-416, type 1, cl 3 federal specification single treatment response         Head Hole Configuration Style:         Round    <	Right-hand	
Fastener Length:         0.875 inches         Head Style:         Fillister         Head Diameter:         Between 0.250 inches and 0.270 inches         Head Height:         Between 0.106 inches and 0.113 inches         Hole Diameter:         0.046 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thready Qty Per Inch (tpi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness Rating:         Between 26.0 rockwell c and 32.0 rockwell c         Screw Material:         Steel comp 8630         Screw Surface Treatment:         Cadmium         Screw Surface Treatment:         Cadmium         Qrep-416, type 1, cl 3 federal specification single treatment response         Aread Hole Configuration Style:         Round         Thread Series Designator:	Thread Length:	
Ara Sro Inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.046 inches Hole Quantity: 1 Thread Jameter: 0.164 inches Hole Quantity: 1 Thread Y Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment: Qap-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Between 0.725 inches an	10.844 inches
Head Style:         Fillister         Head Diameter:         Between 0.250 inches and 0.270 inches         Head Height:         Between 0.106 inches and 0.113 inches         Hole Diameter:         0.046 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thread Diameter (pi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness Rating:         Between 26.0 rockwell c and 32.0 rockwell c         Screw Material:         Steel comp 8630         Screw Material Specification single material response or an-s-9 military standard single material response         Screw Surface Treatment:         Cadmim         Quep-416, type 1, cl 3 federal specification single treatment response         Round         Thread Series Designator:	Fastener Length:	
Filiater Head Diameter: Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 Inches Hole Quantity: 1 Thread Diameter: 0.164 Inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Stel comp 8630 Screw Material Stel comp 8630 Screw Surface Treatment Specification single material response or an-s-9 military standard single material response Screw Surface Treatment Specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	0.875 inches	
Head Diameter:         Between 0.250 inches and 0.270 inches         Head Height:         Between 0.106 inches and 0.113 inches         Hole Diameter:         0.046 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thready Qty Per Inch (tpi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness Rating:         Between 26.0 rockwell c and 32.0 rockwell c         Screw Material:         Steel comp 8630         Screw Material         Mih-s-6050 military specification single material response or an-s-9 military standard single material response         Screw Material Specification:         Mil-s-6050 military specification single treatment response         Cardmium         Screw Surface Treatment:         Cadmium         Qrep-416, type 1, cl 3 federal specification single treatment response         Head Hole Configuration Style:         Round         Thread Series Designator:	Head Style:	
Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Thread You Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Fillister	
Head Height:         Between 0.106 inches and 0.113 inches         Hole Diameter:         0.046 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thread Diameter (pi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness Rating:         Between 26.0 rockwell c and 32.0 rockwell c         Screw Material:         Steel comp 8630         Screw Material:         Mil-s-6050 military specification single material response or an-s-9 military standard single material response         Screw Surface Treatment:         Cadmium         Screw Surface Treatment Specification:         Qu-p-416, type 1, cl 3 federal specification single treatment response         Head Hole Configuration Style:         Round         Thread Series Designator:	Head Diameter:	
Between 0.106 inches and 0.113 inches Hole Diameter: 0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Thread Diameter: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material: Steel comp 8630 Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Between 0.250 inches an	1 0.270 inches
Hole Diameter:         0.046 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.164 inches         Hole Quantity:         1         Thready Qty Per Inch (tpi):         36         Min. Tensile Strength (psi):         125000 pounds per square inch         Hardness Rating:         Between 26.0 rockwell c and 32.0 rockwell c         Screw Material:         Steel comp 8630         Screw Material:         Steel comp 8630         Screw Surface Treatment:         Cadmium         Screw Surface Treatment:         Cadmium         Screw Surface Treatment Specification single treatment response         Head Hole Configuration Style:         Round         Thread Series Designator:	Head Height:	
0.046 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Between 0.106 inches an	10.113 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round	Hole Diameter:	
Cross recess type 1 Thread Diameter: 0.164 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	0.046 inches	
Thread Diameter: 0.164 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Internal Drive Style:	
0.164 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification Aread Hole Configuration Style: Round Thread Series Designator:	Cross recess type 1	
Hole Quantity: 1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Thread Diameter:	
1 Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	0.164 inches	
Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Hole Quantity:	
36 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	1	
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Thready Qty Per Inch (tj	i):
125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	36	
Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round	Min. Tensile Strength (p	si):
Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	125000 pounds per squar	e inch
Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Hardness Rating:	
Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Between 26.0 rockwell c	nd 32.0 rockwell c
Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Screw Material:	
Screw Material Specification: Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Steel comp 8630	
Mil-s-6050 military specification single material response or an-s-9 military standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	-	tion:
Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:		
Screw Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:		
Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:	Cadmium	
Qq-p-416, type 1, cl 3 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:		t Specification:
Head Hole Configuration Style: Round Thread Series Designator:		-
Round Thread Series Designator:		
Thread Series Designator:		-
		or:
-		
Shelf Life:		
N/a		

## NSN 5305-00-150-9464

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

