

View Online at <https://aerobasegroup.com/nsn/5305-00-150-9579>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.811 inches and 1.000 inches

**Fastener Length:**

Between 1.344 inches and 1.391 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.036 inches and 1.145 inches

**Internal Drive Style:**

Cross recess type ii

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

**Screw Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6758 spec.