NSN 5305-00-150-9779

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-150-9779 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.126 inches and 0.188 inches **Fastener Length:** Between 0.156 inches and 0.188 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.249 inches and 0.279 inches **Head Height:** Between 0.048 inches and 0.058 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel or steel comp 1010 **Screw Material Specification:** Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No