NSN 5305-00-151-0353

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-0353

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.375 inches |
| Fastener Length: |
| 0.375 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.292 inches and 0.313 inches |
| Head Height: |
| Between 0.123 inches and 0.130 inches |
| Hole Diameter: |
| 0.047 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 60000 pounds per square inch |
| Screw Material: |
| Steel comp 1010 |
| Screw Material Specification: |
| Qq-s-633 federal specification single material response |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 1 type and 5s style |
| Shelf Life: |
| N/a |

NSN 5305-00-151-0353Machine Screw - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

Demilitarization:

No

Fiig:

A500d0