
## NSN 5305-00-151-0387

Machine Screw - Page 1 of 2





Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.438 inches and 0.500 inches

Fastener Length:

0.500 inches

**Head Style:** 

Fillister

Head Diameter:

Between 0.208 inches and 0.226 inches

**Head Height:** 

Between 0.089 inches and 0.096 inches

Hole Diameter:

0.046 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

**Hole Quantity:** 

1

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

**Screw Material:** 

Steel or steel comp 1010

**Screw Material Specification:** 

Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal

specification 2nd material response

Screw Surface Treatment:

Cadmium

**Screw Surface Treatment Specification:** 

Qq-p-416, type 1, cl 3 federal specification single treatment response

Head Hole Configuration Style:

Round

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

## NSN 5305-00-151-0387

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

