

View Online at <https://aerobasegroup.com/nsn/5305-00-151-2342>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.388 inches and 0.438 inches

Fastener Length:

0.438 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.225 inches and 0.252 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.125 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

55000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Copper alloy 220 or copper alloy 230 or copper alloy 240 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 794 or copper alloy 260 or copper alloy 268 or copper alloy 270 or copper alloy 274 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 462 or copper alloy 464 or copper alloy 482

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 cl4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.