NSN 5305-00-151-2722

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-2722

The LOID				
Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 1.289 inches and 1.454 inches				
Fastener Length:				
1.500 inches				
Head Style:				
Fillister				
Head Diameter:				
Between 0.389 inches and 0.414 inches				
Head Height:				
Between 0.161 inches and 0.170 inches				
Hole Diameter:				
0.062 inches				
Internal Drive Style:				
Cross recess type 1				
Thread Diameter:				
0.250 inches				
Hole Quantity:				
1				
Thready Qty Per Inch (tpi):				
28				
Min. Tensile Strength (psi):				
125000 pounds per square inch				
Hardness Rating:				
Between 26.0 rockwell c and 32.0 rockwell c				
Screw Material:				
Steel comp 8630				
Screw Material Specification:				
Mil-s-6050 military specification single material response or an-s-9 military standard single material response				
Screw Surface Treatment:				
Cadmium				
Screw Surface Treatment Specification:				
Qq-p-416, type 1, cl 3 federal specification single treatment response				
Head Hole Configuration Style:				
Round				
Thread Series Designator:				
Unf				
Shelf Life:				
N/a				

NSN 5305-00-151-2722

Machine Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.