

View Online at <https://aerobasegroup.com/nsn/5305-00-151-2988>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.750 inches

**Fastener Length:**

3.000 inches

**Head Style:**

Round

**Head Diameter:**

Between 0.443 inches and 0.472 inches

**Head Height:**

0.175 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Screw Material:**

Copper alloy 220 or copper alloy 230 or copper alloy 240 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 794 or copper alloy 260 or copper alloy 268 or copper alloy 270 or copper alloy 274 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 462 or copper alloy 464 or copper alloy 482

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 cl4 military specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

3 type and 1c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.